



MASTER PL-C 2 Pin

MASTER PL-C 13W/865/2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

General Information				
Cap-Base	G24D-1 [G24d-1]			
Life To 10% Failures (Nom)	6500 h			
Life to 50% Failures (Nom)	10000 h			
LSF 2000 h Rated	99 %			
LSF 4000 h Rated	98 %			
LSF 6000 h Rated	92 %			
LSF 8000 h Rated	78 %			
Light Technical				
Color Code	865 [CCT of 6500K]			
Luminous Flux (Nom)	845 lm			
Luminous Flux (Rated) (Nom)	845 lm			
Color Designation	Cool Daylight			
Correlated Color Temperature (Nom)	6500 K			
Luminous Efficacy (rated) (Nom)	63 lm/W			
Color Rendering Index (Nom)	80			
LLMF 2000 h Rated	90 %			
LLMF 4000 h Rated	85 %			
	81 %			
LLMF 6000 h Rated	81 %			

LLMF 8000 h Rated	77 %
Operating and Electrical	
Power (Nom)	13.4 W
Lamp Current (Nom)	0.170 A
Temperature	
Design Temperature (Nom)	28 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	2 Pins
Approval and Application	
Energy Efficiency Label (EEL)	В
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	17 kWh

Datasheet, 2020, March 19 data subject to change


MASTER PL-C 2 Pin

Product Data	
Full product code	871150063523500
Order product name	MASTER PL-C 13W/865/2P 1CT/5X10BOX
EAN/UPC - Product	8711500635235
Order code	927904886502
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	50
Material Nr. (12NC)	927904886502
Net Weight (Piece)	53.600 g
ILCOS Code	FSQ-13/65/1B-I-G24d=1

Warnings and Safety


Dimensional drawing




PL-C 13W/865/2P

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/865/2P	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
1CT/5X10BOX					

Photometric data




LDPB_PLC2P_865-Spectral power distribution B/W




MASTER PL-C 2 Pin

Lifetime





LDLE_PLC2P_0001-Life expectancy diagram



LDLM_PLC2P_0001-Lumen maintenance diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.